

Picurator cu compensare Irritec Light PC

Lungimi maxime recomandate ale randurilor, in metri, in functie de presiune

Tub diametru exterior 16 mml, grosime 1 mm, Kd=0,4									
Debit picurator lph	Presiune bar	Distanța între picuratoare (m)							
		0,2	0,3	0,4	0,5	0,6	0,75	1,0	1,5
1,1	1	94	122	147	169	190	228	263	341
	2	158	205	247	284	320	384	443	573
	3	194	252	303	349	392	472	544	704
	4	221	287	345	398	447	537	620	801
2,1	1	63	81	98	113	127	152	176	227
	2	105	137	164	190	213	256	295	382
	3	129	168	202	233	262	314	362	469
	4	147	191	230	265	298	358	413	535
3,8	1	43	55	67	77	86	95	120	155
	2	71	93	112	129	145	160	201	261
	3	87	114	137	158	178	197	247	320
	4	100	130	156	180	203	224	281	365
7,8	1	27	35	42	49	55	63	76	98
	2	45	59	71	82	92	106	127	165
	3	55	72	87	100	113	130	156	203
	4	63	82	99	114	128	148	178	231

Tub diametru exterior 20 mm, grosime 1,2 mm Kd=0,2									
Debit picurator lph	Presiune bar	Distanța între picuratoare (m)							
		0,2	0,3	0,4	0,5	0,6	0,75	1,0	1,5
1,1	1	139	181	218	251	282	339	391	506
	2	234	304	366	422	474	570	657	850
	3	288	374	449	518	583	700	806	1045
	4	328	426	512	591	664	797	919	1190
2,1	1	93	121	145	167	188	226	260	337
	2	156	203	244	281	316	380	438	567
	3	192	249	299	345	388	467	538	697
	4	218	284	341	394	442	532	613	793
3,8	1	63	82	99	114	128	141	178	230
	2	106	138	166	191	215	238	299	387
	3	130	169	204	235	264	292	367	475
	4	148	192	232	268	301	332	418	541
7,8	1	40	52	63	72	81	94	112	146
	2	67	87	105	121	136	157	189	245
	3	82	107	129	149	167	193	232	301
	4	93	122	147	169	190	220	264	342

- Presiune = Presiunea de lucru in bar • Inclinatie = 0
- Presiune minima functionare = 0,7 bar

Picuratorul Irritec Light-PC are iesire multifunctionala IDROP™

Permite montarea oricarui tip de manifold sau tub capilar Irritec (6 x 4 mm).

